

(19) World Intellectual Property Organization  
International Bureau



19 JUL 2004



(43) International Publication Date  
31 July 2003 (31.07.2003)

PCT

(10) International Publication Number  
**WO 03/062678 A1**

(51) International Patent Classification<sup>7</sup>: **F16H 63/20**

(21) International Application Number: PCT/EP03/00723

(22) International Filing Date: 24 January 2003 (24.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0201658.2 25 January 2002 (25.01.2002) GB

(71) Applicant (for all designated States except US): **EATON CORPORATION** [US/US]; Eaton Center, 1111 Superior Avenue, Cleveland, OH 44114 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HEATHCOTE,**

Ian [GB/GB]; 133 John Street, Biddulph, Stoke on Trent, Staffordshire ST8 6HP (GB). **JACKSON, Graeme, Andrew** [GB/GB]; 20 Greensmithway, Westoughton BL5 3BR (GB).


(74) Agent: **ABEL, Thomas**; Rüger, Barthelt & Abel, Weber-gasse 3, 73728 Esslingen (DE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: GEARSHIFT APPARATUS FOR MULTI-GEAR TRANSMISSIONS



(57) Abstract: A gear selection mechanism with three, four or more shift rails (28-31) has a shift rail selector element (46) for axially moving a selected shift rail. The shift rails are provided with cutouts (42a-42d), which form a course through which the shift rail selector element can move. Two tongues (47, 48) of the selector element are located in the shifting course. The cutouts in the shift rails are laterally spaced apart from each other such that one of the tongues of the forked shift rail selector element can only come into engagement with respectively one shift rail. Adjoining cutouts are either arranged so close together that a cutout is placed into the space between the tongues while one of the tongues is in engagement with the other cutout, or that one cutout is located outside of the fork formed by the tongues, while one of the tongues is in engagement with a cutout.

WO 03/062678 A1



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,  
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

— before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*

Gearshift Apparatus for Multi-Gear Transmissions

The invention relates to a gearshift mechanism for multi-ratio transmissions.

Multi-ratio transmissions of the type with several shift rails, which are arranged next to each other and support respectively one shift fork for engaging and disengaging gears, are known. Examples are to be taken from US patent No. 4,104,929. The shift rails of such transmissions are seated in an orientation parallel in respect to each other and displaceably longitudinally within the transmission housing. In this case each shift rail has a neutral position and at least one position in which it is moved out of the latter (in gear position). The shift rails have cutouts to be engaged by a shift finger. When all shift rails are in their neutral position, cutouts are aligned with each other, so that the shift finger can be moved transversely in respect to the shift rails through the cutouts, (the cross-gate movement).

To actuate individual shift rails, the shift finger is moved into the cutout of a selected shift rail. A subsequent movement of the shift finger in respect to the longitudinal (into gear) direction of the respective shift rail displaces the latter accordingly. By means of this the associated shift clutch is actuated via the shift fork associated with the shift rail. In this case each shift fork is preferably responsible for a pair of gears, for example reverse gear/first gear, or second/third gear. The pairs of gears are arranged in a conventional H-shift pattern or HH-shift pattern at ends of a branch of the shift pattern which are located opposite each other. In this case the change of the shift finger from one shift rail to the other shift rail, i.e. a lateral movement of the shift finger, corresponds to a change in the branches of the shift pattern, for example from two/three to four/five. Thus the path of the shift finger from shift rail to shift rail determines the lateral shifting travel at the shift finger and consequently of a shift lever connected to the shift finger. With transmissions of increased size, which can have increased shift rail distances, long shifting travels can therefore occur.

#### Summary of the invention

Based on this, it is the object of the invention to provide a gearshift apparatus, which permits a reduction of the lateral shifting travel (cross-gate travel).

This and other objects are attained by means of the gearshift mechanism according to claim 1.

A gear selection mechanism with three, four or more shift rails has a shift rail selector element for axially moving a selected shift rail. The shift rails are provided with cutouts, which form a course through which the shift rail selector element can move transversely in respect to the

shift rails. The shift rail selector element has two tongues, which are arranged parallel with each other and spaced apart from each other. The tongues are located in the shifting course formed by the cutouts. In this case the cutouts in the shift rails are laterally spaced apart from each other in such a way that one of the tongues of the shift rail selector element can only come into engagement with respectively one shift rail. Adjoining cutouts are either arranged so close together that a cutout is placed into the space between the tongues while one of the tongues is in engagement with the other cutout, or that one cutout is located outside of the fork formed by the tongues, while one of the tongues is in engagement with a cutout.

A particular advantage of such an arrangement of the shift rails and their cutouts and of the use of a pair of tongues, i.e. a forked shift rail selector element, lies in that the shift rail selector element can be given a particularly short transverse (cross-gate) travel. Because of this the transmission is given a shift feel and a short shifting path as in a passenger car, even if it is larger than a conventional passenger car transmission. But with a known selection finger the path must be greater in order to reach one of the three or four shift rails.

The gearshift mechanism in accordance with the invention makes possible a clearly reduced lateral shifting travel (cross-gate travel). The reduced travel is an advantage in passenger cars and can give the transmission of a truck a shift travel similar to that of a passenger car. The invention, which basically can be used in all transmissions with several shift rails, is particularly suited for use in medium-size transmissions in a torque range between 1000 and 2000 Nm.

Shortening of shift lever travel is achieved in that the shift rail selector element is provided with two spaced-

apart selector tongues, which can be moved transversely through a shifting course constituted by interlocking elements of the shift rail. The interlocking elements are for example cutouts in the shift rails, or in fork-like protrusions thereof. When these cutouts are positioned next to each other, they form the shifting course.

While the first selector tongue engages with one of the two shift rails and the selector tongue serves two adjoining shift rails, which for example, constitute a pair of shift rails, the second selector tongue is engageable with a third shift rail, as well as a fourth shift rail, which can be optionally provided and which then makes a pair with the third shift rail. The distance between the interlocking elements of the shift rails within a pair of shift rails is clearly less than the lateral distance of the two pairs of shift rails from each other.

The gearshift mechanism has at least three shift rails. If required, it can have four shift rails arranged in two pairs (or even more). The principle of the invention can be applied in particular to an arrangement in which all shift rails are arranged next to each other, and the shift rail selector element moves on a straight path laterally in respect to the shift rails for selecting them. Alternatively, the principle of the invention can be applied in connection with shift rails arranged next to each other on a curved line, for example an arc of a circle, in which case the shift rail selector tongue then moves on a path in the shape of an arc of a circle. In both cases a reduction of the travel of the shift rail selector element required for selecting a shift rail is achieved.

A preferred embodiment of a gearshift mechanism has shift rails of rectangular cross section. These permit a particularly short lateral distance and therefore short shift lever travel. This in particular, if the interlocking

elements, measured in the first direction (transverse direction) have a width which is less than the width, measured in the same direction, of the respective shift rail. In a preferred embodiment, the width of the interlocking elements is approximately half the width of the shift rails. By means of this a reduction of the shifting travel by almost one third results, compared with gearshift mechanisms of the conventional type.

A blocking device (interlocking assembly) is preferably a part of the gearshift mechanism, which assures that only one shift rail can be moved out of its center neutral position into an engagement position by means of a linear movement. The blocking device has a blocking element (interlocking element), which is preferably formed by a transverse bolt or transverse rib extending transversely in respect to the shift rails. This blocking element follows the transverse movement of the shift rail selector element, and to this end it is fixedly connected with it in respect to the transverse direction (first direction). The blocking element has one or several cutouts, which act together with projections or cutouts formed on the shift rails. For example, the blocking element can extend through a groove formed by cutouts in the shift rails. Only that shift rail, which is aligned with the cutout in the blocking element, can be moved. A mechanical blockage of the gearshift mechanism is caused in this way, so that erroneous simultaneous actuations engagement of two gears can be prevented.

The shift rail selector element can be embodied as a pivot finger with a forked end, or as a slider with two selector tongues (tongues). In the latter instance, the shift rail selector element is preferably seated in a support, which is movable in respect to the shift rails, so that it is displaceable in relation to the longitudinal direction of the shift rails. The support can be resiliently biased in respect to its center position. The center position is preferably a

center neutral position. However, it can also be determined differently from this.

Further details of advantageous embodiments of the invention ensue from the dependent claims, the drawings and/or the description.

#### Brief Description of the Drawings

Fig. 1 illustrates a transmission in a schematic representation,

Fig. 2 illustrates a gearshift mechanism in a perspective schematic representation,

Fig. 3 illustrates a gearshift mechanism with the reverse gear shift rail selected, in a cross-sectional representation,

Fig. 4 illustrates the gearshift mechanism of Fig. 3 with a second shift rail selected, in a cross-sectional representation,

Fig. 5 illustrates the gearshift mechanism of Figs. 3 and 4 with a third shift rail selected, in a cross-sectional representation,

Fig. 6 illustrates the gearshift mechanism of Figs. 3 to 5 with a fourth shift rail selected, in a cross-sectional representation,

Fig. 7 is a schematic illustration of the geometric relationships between the shift rails and their interlocking elements with the selector tongues of the gearshift selector element in a schematic representation (at a highly abstract level),



Fig. 8 illustrates the embodiment of a shift rail in a schematic and sectional perspective representation,

Fig. 9 illustrates a gear cassette of the gearshift mechanism in accordance with the invention in a perspective representation,

Fig. 10 illustrates a gearshift mechanism with a pivotable shifting finger and four shift rails in a partially sectional perspective representation,

Fig. 11 illustrates the shift rail selector element, which is a part of the gearshift mechanism in accordance with Fig. 10, in a perspective representation.

Description of Embodiments of the Gearshift Mechanism in Accordance with the Invention:

A five-gear manual change gear transmission 1 is illustrated in Fig. 1, which has an input shaft 2, a main shaft 3, an output shaft 4 and a countershaft 5, arranged parallel with the main shaft 3. The shafts are rotatably seated in a transmission housing, not represented in detail. The input shaft 2 has an input gear 6, which is connected, fixed against relative rotation, with the latter and meshes with a counter shaft gear 7, by means of which the countershaft 5 is driven from the direction of the input shaft 2. Further gear wheels form gear wheel pairs 8, 9, 10, 11, with which countershaft gears 13, 14, 15, 16, connected fixed against relative rotation with the countershaft 5, and main shaft gears 17, 18, 19, 20 rotatably seated on the main shaft 3, are respectively associated. With an idler gear, not further illustrated, a further countershaft gear 21 meshes with a further main shaft gear in order to form a gear set for the reverse gear.

To select gears, clutches 23a, 24a, 25a, for example

of the jaw clutch type, are provided, which can be of the synchronized type or the non-synchronized type, depending on the requirements. In its center position, the clutch 23a does not provide a coupling connection. If in Fig. 1 it is  
5 displaced toward the left, it couples the input shaft 2 with the main shaft 3 and constitutes the direct (fifth) gear. If it is displaced toward the right, it couples the main shaft gear 17 with the main gear, so that the gear wheel pair 8 is activated (transfers torque), so that the fourth gear is  
10 selected. Correspondingly, the clutch 24a is used for the selection between the second and third gears, and the clutch 25a for the selection between the first gear and reverse. Thus, the transmission represented provides five forward  
15 gears and one reverse gear. If required, further gear wheel pairs can be provided in order to create a seven or a nine gear transmission. Moreover, it is possible to provide front-mounted or rear-mounted groups that is auxiliary transmissions of the splitter type, or the range type, or the  
20 splitter/range type.

In the present exemplary embodiment, three shift forks 23, 24, 25 are provided, which are supported by the shift rails 28, 29, 30 of a gearshift mechanism 32, and are used for actuating the clutches 23a, 24a, 25a, i.e. to move them  
25 from their center neutral position into their left engagement position or into their right engagement position. Such a gearshift mechanism is represented in Fig. 2. The gearshift mechanism 32 in Fig. 2 is intended for a seven or nine gear transmission and has, in addition to the three shift rails  
30 28, 29, 30, a further shift rail 31. Correspondingly, a further shift fork 26 is provided, which is supported by the shift rail 31.

The shift rails 28, 29, 30, 31 have an essentially  
35 rectangular cross section and are arranged next to each other in relation to a first direction (X-X direction). Their ends are displaceably seated in bearing blocks 33, 34 in the

second direction (Y-Y direction).

The shift rail 29 has been separately illustrated by way of example in Fig. 8. The shift rail 29 has two flat sides 35b, 36b, which are located opposite each other and point away from each other, which are respectively followed at the top and bottom by narrow sides 37b, 38b. The corresponding flat sides and narrow sides of the shift rails 28, 30 and 31 have the respective letter index a, c, or d (Fig. 3). A trough-like depression 39b extends through the flat side 36b as far as to the narrow side 37b. The shift rail 29 has a narrow wall area 41b in the area of this depression 39b, into which a cutout 42b, used as an interlocking element, and a cutout 43b used for blocking the shift rail, have been cut. Corresponding cutouts 42a, 42c and 42d are provided in the corresponding wall areas 41a, 41c, 41d of the other shift rails 28, 30, 31. This correspondingly applies to the cutouts 43a, 43c and 43d, which have only been indicated in Fig. 2. The narrow sides 38 of the shift rails 28, 29, 30, 31 are arranged on a common plane, so that the cutouts 42a, 42b, 42c, 42d form a shifting course.

As can be seen in Fig. 3, the shift rails 28, 29, 30, 31 are arranged in pairs, wherein the shift rails 28, 29 are embodied in a mirror-reversed manner and form a first shift rail pair 44. The shift rails 30, 31 are also embodied in a mirror-reversed manner and form a second shift rail pair 45.

The shift rails 28, 29, 30, 31 are closely spaced apart within a shift rail pair 44, 45, wherein the shift rail pairs 44, 45 are at a greater distance from each other. This can be seen in Fig. 7. The distance A between the wall centers of two adjoining wall areas 41a, 41b determines a grid dimension which is indicated in Fig. 7 by means of grid lines R1 to R6. The wall areas 41b and 41c are apart from each other by three grid lines (four times the grid distance A), while the wall areas 41c and 41d are only spaced apart by a single distance A. In this way a clear space 49 of a width of twice A remains

between the edge areas 41b, 41c.

A shift rail selector element 46 is assigned to the shift rails 28, 29, 30, 31, which has two tongues 47, 48, which are arranged parallel with each other. The latter fit with play into the respective cutout 42a, 42b, 42c, 42d. In the transverse direction, the tongues 47, 48 are of a thickness which approximately matches the thickness of the wall sections 41a, 41b, 41c, 41d, or is slightly less than these. The center distance between the tongues 47, 48 corresponds to double the grid dimension A. Therefore the clear distance between the tongues 47, 48, i.e. the space between them, is slightly wider than each wall 41a, 41b, 41c or 41d. Thus the clear distance is also greater than A. In the embodiment in accordance with Fig. 7, the outer distance, i.e. the distance between the outsides of the tongues 47, 48 which point away from each other, is less than the distance between the two wall areas 41b, 41c, i.e. less than three times A. Therefore no center position, in which its tongues 47, 48 are not in contact with any shift rail, exists for the shift rail selector element 46. If such a center position is desired, in which the shift rail selector element 46 has not selected any shift rail, the distance between the shift rails 29, 30 can be increased by one grid dimension without any other functional losses.

The spacings and dimensions follow the equations:

$$B < C \text{ and}$$

$$E < D,$$

wherein B = wall thickness (Fig. 7)

C = spacing between tongues 47, 48

D = spacing 49

E = thickness of tongue (47 or 48) plus spacing therebetween.

On its top, the shift rail selector element 46 has a

forked end 51, represented in Fig. 9, which can be engaged by a conventional shift finger. The shift rail selector element 46 is furthermore seated, displaceable in the Y-Y direction called the second direction, in a support 52 embodied as a carriage. The Y-Y direction corresponds to the longitudinal direction of the shift rails 28, 29, 30, 31.

The support itself is seated in a cassette housing 53 and is displaceable in the X-X direction, i.e. transversely to the shift rails, but cannot be shifted in the X-X direction. The support 52 has a slit 54 used as a guide means, through which the end 51 of the shift rail selector element 46 passes. The support 52 is braced by means of appropriate guide cheeks 56, 57 on the inside of the cassette housing 53, which is approximately rectangular in a view from above.

The support 52 furthermore has a blocking element 58 in the form of a rib extending in the X-X direction. The latter enters into the cutouts 43a, 43b, 43c and 43d of the shift rails 28, 29, 30, 31. Two cutouts 60, 61 have been formed next to each other in the blocking element 58, each of which can release a shift rail. The positions of the cutouts 60, 61 can be seen in Fig. 7. They are respectively two grid distances A wide and are distant from each other by one grid distance A.

As can be seen in particular in Fig. 9, the support 52 is maintained in a desired initial position, for example a center position, by means of a prestressing device (bias means) 62. Part of the prestressing device 62 is for example a pin 63 (shaft), visible in Fig. 5, which extends away from the support 52 in the X-X direction and is fixedly connected with it. Near an appropriate opening 66, the pin 63 extends through an intermediate wall 65 formed in the cassette housing 53. Furthermore, a further opening 67, aligned with the opening 66, is provided in the housing wall of the

cassette housing 53. A pressure spring 68 is seated on the pin 63 and is supported on the one end by means of two end plates 69, 70 (washers) on an annular shoulder 71 of the pin 63, and on the other end by a snap ring 72. Furthermore, the snap ring 72 holds an eye 73 seated on the pin 63, whose exterior diameter matches the interior diameter of the two end plates 69, 70. The eye 73 is connected axially fixed with the pin 63. It has a section 74 of increased diameter, whose diameter is greater than the interior diameter of the pressure plates 69, 70. The distances between the respective fronts of the section 74 and the pressure plate 69, or 70, determine the maximum travel path of the pin 63, and therefore of the support 52, in the X-X direction. In the position of rest, the pressure plates 69, 70 are in stationary contact at the intermediate wall 65 and the cassette housing.

If necessary, the support 52 can be provided with a transverse bore 75, in which a spring-loaded stop mechanism 76 can be provided, for example to establish an obstacle which must be overcome if it is intended to actuate a shift rail assigned to the reverse gear, for example the shift rail 30 (in a three shift rail mechanism) or the shift rail 31 (in a four shift rail mechanism).

The gearshift mechanism 32 operates as follows:

When in operation, a shift finger engages the forked end 51 of the gearshift mechanism 32 which is visible, for example, in Fig. 5. The support 52 has been put into a position of rest by the pressure spring 58, in which the tongue 48 coincides (is in registration with) with the cutout 42b of the shift rail 29. If it is now intended to select the gear which is to be actuated by the shift rail 31, a shift finger 77, which is only shown in dash-dotted outline in Fig. 3 and enters into the slit 54, displaces the support 52, and therefore also the shift rail selector element 46,

into the position illustrated in Fig. 3. The tongue 47 comes into engagement with the shift rail 31, while the tongue 48 stays in the space between the shift rails 29, 30. This state is again illustrated in Fig. 7. As can be seen, the cutout 60 of the blocking element 58 here unblocks the shift rail 31 - all other shift rails 28, 29, 30 are blocked. A movement of the shift finger 77 in the Y-Y direction can now move the shift rail 31 in the longitudinal direction in order to engage the desired gear. The position of the support 52 is fixed through the effect of the prestressing device 62. The section 74 of the sleeve 73 is supported on the intermediate wall 65 via the end plate 69 (washer).

If the shift rail 30 is to be actuated, the shift rail selector element 46 must first be moved in such a way that the shift rail 31 is returned into its neutral position. In this position all cutouts 43a, 43b, 43c, 43d are aligned with each other. The shift rail selector element 46 can therefore be moved in the X-X direction. Its tongue 47 leaves the cutout 42d and enters into the cutout 42c. The tongue 48 continues to remain in the clear space 49. The position taken is illustrated in Fig. 4. Only the shift rail 30 can be displaced, the shift rails 28, 29, 31 are blocked by the blocking element 58. In this state the shift rail 30 can be moved for engaging and disengaging the appropriate gear. The shift rail selector element 46 can be moved further toward the right from this neutral position, in which it is coupled with the shift rail 29 and in which the prestressing device 62 is relaxed.

To engage the gears connected with the shift rail 28, the shift rail selector element 46 is moved into the position illustrated in Fig. 6 by means of the shift finger 77, in which the tongue 48 sits in the cutout 42a, while now the tongue 47 is located in the clear space. As can be seen, this takes place against the prestress of the prestressing device 62.

The tongue 47 is assigned to the shift rail pair 44, while the tongue 48 is assigned to the shift rail pair 45. The distance between the shift rail pairs 44, 45 can be  
5 arbitrarily increased. However, in the disclosed embodiment it is possible to achieve a particularly short shifting travel in the X-X direction. Its length corresponds to only four grid distances A.

10 Fig. 11 illustrates a modified embodiment of a gearshift mechanism 132 in accordance with the invention. Part of this are again four shift rails 128, 129, 130, 131, to which a shift tower 180 (shift tower assembly) is assigned. The latter has a housing 181, in which a shift  
15 lever 182 is pivotably seated by means of a pivot bearing 183. Pressure elements 184, 185 acting below its pivot center can prestress the shift lever 182 toward its center.

20 Its lower end 186 passes through a blocking and guide plate 187, which for this purpose has a slit 188 extending in the Y-Y direction. The blocking and guide plate itself is guided in such a way that it is only displaceable in the X-X direction, but not in the Y-Y direction. It can have a blocking element 158 at a location distant from the slit 188,  
25 which essentially corresponds to the blocking element 58 in Fig. 7.

The shift lever 182 is separately illustrated in Fig. 12. Below a bearing ball 189 it has a wedge section 190, on  
30 which the pressure elements 184, 185 (Fig. 11) act. A shift rail selector element 146 with two tongues 147, 148, which are used as selector tongues for the shift rails 128, 129, 130, is embodied below the wedge section 190. These are embodied corresponding to the shift rail 29 in accordance  
35 with Fig. 8. The geometric relationships correspond to those described in connection with Fig. 7.



Claims:

1. A gearshift mechanism for multi-gear ratio  
5 transmissions, the mechanism having:

a shift rail selector element (46), provided with a  
first selector tongue (47) and a second selector tongue (48),  
wherein the selector tongues (47, 48) are maintained at a fixed  
10 spaced apart distance from each other,

a first shift rail (28) which is connected to a first  
shift fork (23) for engaging and disengaging gear ratios by  
clutch means (23a), the first shift rail (28), having an  
15 interlocking element (42a) for the selective engagement of the  
second selector tongue (48),

a second shift rail (29) which is connected to a second  
shift fork (24) for engaging and disengaging gear ratios by  
20 clutch means (24a), the second shift rail (29), having an  
interlocking element (42b) for the selective engagement of the  
second selector tongue (48),

2. The gear shift mechanism according to claim 1  
25 additionally comprising at least a third shift rail (30) which  
is connected to a third shift fork (25) for acting on third  
clutch means (25a), the third shift rail (30), having an  
interlocking element (42c) for the selective engagement of the  
first selector tongue (47).

30

3. The gear shift mechanism according to claim 2,  
characterized in that a first group includes two shift rails  
and a second group contains at least one shift rail.

35

4. The gear shift mechanism according to claim 3,  
characterized in that the shift rails are in two groups, each  
group containing two shift rails.

5        5. The gear shift mechanism according to claim 1,  
characterized in that each shift rail has engagement regions  
for engagement with a selector tongue depending from a selector  
element.

10       6. The gear shift mechanism according to claim 1,  
characterized in that the distance between the selector tongues  
(47, 48) is greater than the distance between two adjacent  
interlocking elements.

15       7. The gear shift mechanism according to claim 1,  
characterized in that which the distance between the selector  
tongues is smaller than the distance between two spaced apart  
interlocking elements.

20       8. The gearshift mechanism according to claim 1,  
characterized in that a plurality of shift rails is provided  
grouped into pairs of adjacent shift rails, the groups being  
spaced apart wherein a plurality of selector tongues is  
provided each of which being individually associated to one of  
the pairs of the shift rails.

25       9. The gearshift mechanism according to claim 1,  
characterized in that the selector element is movable in a  
cross-gate travel direction transversely to the shift rails and  
in an into gear direction longitudinally to the shift rails.

30       10. The gearshift mechanism according to claim 1,  
characterized in that all interlocking elements (42a, 42b, 42c,  
42d) have a width (A), measured in the first direction (X-X),  
which is less than the width of the respective shift rail (28,  
29, 30, 31) measured in the same direction (X-X).

35       11. The gearshift mechanism according to claim 10,  
characterized in that the width of each of the interlocking  
elements (42a, 42b, 42c, 42d) is approximately half the width

of each of the shift rails (28, 29, 30, 31).

12. The gearshift mechanism according to claim 1, characterized in that the selector tongues (47, 48) of the shift rail selector element (46) are tongues, whose width essentially corresponds to the width of the interlocking elements (42a, 42b, 42c, 42d).

13. The gearshift mechanism according to claim 1, characterized in that the shift rail selector element (46) is connected with a blocking element (58), which blocks all shift rails (28, 29, 30, 31) in a center position in relation to the second direction (Y-Y) when both selector tongues (47, 48) of the shift rail selector element (46) are in at least partial engagement with the shift rails (28, 29, 30, 31).

14. The gearshift mechanism according to claim 1, characterized in that the shift rail selector element (46) is connected with a blocking element (58), which releases only the one of all the shift rails (28, 29, 30, 31) for movement in the second direction (Y-Y), whose interlocking element is the only one which is in engagement with the selector tongue.

15. The gearshift mechanism according to claim 13 or 14, characterized in that the blocking element (58) is arranged on a support (52), which is seated displaceably in the first direction (X-X) and in this direction is connected with the shift rail selector element (46), wherein the shift rail selector element (46) is freely movable relative to the support (52) in the second direction (Y-Y).

16. The gearshift mechanism according to claim 1, characterized in that the shift rail selector element (46) is resiliently biased towards its center position by means of at least one spring element (68) at least in the first direction (X-X), in which its selector tongues (47, 48) are not in engagement with the interlocking elements of the shift rails,

or in which its selector tongues (47, 48) are in engagement with the interlocking element (42b) of a selected shift rail (29).

5           17. The gearshift mechanism according to claim 10,  
characterized in that the support (52) has an extension (63) in  
the first direction (X-X), which supports a pressure spring  
(68), which is supported between two driver plates (69, 70),  
which are stretched by the pressure spring (68) between detents  
10 (71, 72) formed on the extension (63), wherein two stationary  
contact faces (65, 53) are assigned to the pressure spring  
(68).

15           18. The gearshift mechanism according to claim 1,  
characterized in that the shift rail selector element (46) is  
seated, movable in the second direction (Y-Y), on a support  
(52), which in turn is seated, displaceable in the first  
direction (X-X), in a housing (53), wherein the shift rail  
selector element (46) has a means (51) for a connection with a  
20 known selector finger (77).






Fig.1











Fig. 4











**Fig.7**








Fig.10




Fig.11

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 03/00723

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 F16H63/20

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 608 877 A (GUSS WALTER ET AL) 2 September 1986 (1986-09-02) figure 1	1-13
X	EP 0 737 827 A (PEUGEOT ;CITROEN SA (FR)) 16 October 1996 (1996-10-16) the whole document	1-3,5-7, 9,12-16
X	EP 0 300 843 A (PEUGEOT ;CITROEN SA (FR)) 25 January 1989 (1989-01-25) the whole document	1,2,5,6, 9,12
X	DE 922 508 C (ZAHNRADFABRIK FRIEDRICHSHAFEN) 17 January 1955 (1955-01-17) the whole document	1,10
A		17

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&\* document member of the same patent family

Date of the actual completion of the international search

6 May 2003

Date of mailing of the international search report

20/05/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Vogt-Schilb, G



**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International Application No  
**PCT/EP 03/00723**

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 4608877	A	02-09-1986	JP	60077214 A	01-05-1985
EP 0737827	A	16-10-1996	FR	2733020 A1	18-10-1996
			DE	69602674 D1	08-07-1999
			DE	69602674 T2	30-09-1999
			EP	0737827 A1	16-10-1996
			ES	2132850 T3	16-08-1999
EP 0300843	A	25-01-1989	FR	2618510 A1	27-01-1989
			DE	3860228 D1	19-07-1990
			EP	0300843 A1	25-01-1989
DE 922508	C	17-01-1955	NONE		